| | | | L E |
|-------|-----|------------------------------|-------------------------------------------------------------|
| ITEM# | QTY | PART # PART TITLE | |
| -1 | 1 | RBW6705G03031-3G-1 | PIN ASSY |
| 2 | 2 | McMaster#3896T31 OR EQUIV. | ALUMINUM WIRE ROPE COMPRESSION SLEEVE 1/16" DIA. X 3/8" LG. |
| 3 | 2 | McMaster#90905A655 OR EQUIV. | 316 SS SPLIT RING 15/16" ID. X 1-1/16" OD. X 1/8" THK. |
| 4 | 1 | CARR-LANE#CL-2-C | NYLON COATED STEEL LANYARD 1/16" DIA. |
| 5 | 1 | NAS1756-12 | REMOVE BEFORE FLIGHT FLAG |

 $\boxed{8}$ (4)

RBW6705G03031-3G M/R BLOCK SIMULATION TOOL 9

В

1) MATERIAL: N/A 2) HEAT TREAT: N/A

3) FINISH: N/A

4) TOLERANCES: X.X = +/- 0.1" / +/- 1°

X.XX = +/-0.01" / +/-0.5° X.XXX = +/-0.005" / +/-0.1°

X.XXX = +/- 0.005" / +/- 0.1"
X.XXXX = +/- 0.005" / +/- 0.05°
PARALLELISM, ECCENTRICITY AND SYMMETRY ABOUT ALL CENTER LINES = +/-0.005"

5) UNITS: INCHES UNLESS OTHERWISE NOTED
6) IDENTIFICATION: N/A
7) ASSEMBLE AS SHOWN
8) ASSEMBLED LANYARD LENGTH MUST BE 6" +/- 1"
9) THE TOOL ASSY MUST BE PACKAGED WITH A DESICCANT BAG INTO A TIGHT FITTING SEALED PLASTIC BAG

| DESIGN KPT | | KPT | DART AEROSPACE LTD | | | |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------------------|--------|-----|---|
| REV. | DESCRIPTION | | ECN# | BY | | |
| | -2 DIM WAS 3.95 IS 3.94. DIM WAS ϕ .56 IS ϕ 0.53. DIM WAS 1.049 IS 0.97. DIM WAS 1.750 IS 1.77. DIM WAS R.049 SPHERE IS SR0.06. DIM WAS ϕ .493 (x2) IS 0. ϕ 472 2 PL. DIM WAS ϕ .248 IS ϕ 0.250-0.249. DIM WAS .24 (x2) IS 0.25. DIM WAS .03x45° IS 0.03 X 45.0° CMF 3 PL. DIM WAS ϕ .452 IS ϕ 0.4525-0.4518. DIM WAS .23 IS 0.20. ADDED FLAT FOR ENGRAVING. ADDED 1.42 MEDIUM DIAMOND KNURL, 0.06, ϕ 0.433, AND R0.79 DIMS. REMOVED MIN. RELIEF, 10°, AND 0.50 DIMS | | | | | |
| С | -1 TRANSFER DRILL HOLE DIM WAS ϕ .116 IS ϕ 0.156 THRU. ADDED 0.25 AND 0.76 DIMS | | | 19-906 | KPT | |
| | ADDED ITEM 3 | | l | | | |
| | ITEM -2 WAS ITEM -3 ITEM 7 WAS ITEM -5 | | | | | |
| | UPDATED DRAWING TEMPLATE | | | | | l |
| | SEE PREVIOUS REVISION FOR MORE INFORMATION | | | | | |

DESIGN KPT DRAWN KPT CHECKED JMH MFG. APPR. APPROVED

TOOL PART # RBW6705G03031-3G

M/R BLOCK SIMULATION TOOL

SHEET 1 OF 3 SCALE NTS

REV. C

COPYRIGHT © 2019 BY DART AEROSPACE LTD


THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

HAWKESBURY, ONTARIO, CANADA

5

3

DATE 2019-09-13



D

